



RED IS THE CONTROL WIRE
CONNECT RED TO BLACK FOR SPEED 3
CONNECT RED TO WHITE FOR SPEED 2
LEAVE RED DISCONNECTED FOR SPEED 1

1. USE COPPER CONDUCTORS ONLY
2. UNIT MUST GROUNDED
3. FOR MOTOR AMPS SEE RATING STICKER ON OUTSIDE OF UNIT.

MOTOR	SPEED 1 (RPM)	SPEED 2 (RPM)	SPEED 3 (RPM)	WHEN VIEW FROM BLADE END
3707-1 / 3708-1	900	600	1200	CCW
3707-2 / 3708-2	900	600	1800	CCW
3707-3 / 3708-3	900	600	1800	CW
3707-4 / 3708-4	1000	1400	1800	CCW
3707-5 / 3708-5	600	1200	1800	CCW

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS .XX+ .XX + 1 DECIMALS .XXX+.XXX ANGLES		CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE		LRC COIL CO		
MATERIAL XX		APPROVALS	DATE			
FINISH --		DRAWN SV	3/26/14	WIRING DIAGRAM D UNITS		
NEXT ASSY USED ON		CHECKED				
APPLICATION		RESP ENG				
DO NOT SCALE DRAWING		MFG ENG		SIZE A	DWG. NO. ES-D	REV. A
		QUAL ENG		SCALE	CAD FILE:	SHEET OF

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF LRC COIL. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF LRC COIL CO. IS PROHIBITED.