



Super Low Profile Unit Cooler (SLP) Physical Data

# Fans	Connections			Dimensions				Weight (lbs)
	Liquid	Suction	Drain (FTP)	A	B	C	D	
1 Fan	1/2 O.D.	7/8 O.D.	7/8 O.D.	47 1/4	23 5/8	35 13/16	-	53
2 Fans	1/2 O.D.	7/8 O.D.	7/8 O.D.	64 1/4	32 1/8	53 1/4	-	80
3 Fans	1/2 O.D.	1 1/8 O.D.	7/8 O.D.	81 1/4	40 5/8	35 13/16	34 13/16	106
4 Fans	1/2 O.D.	1 1/8 O.D.	7/8 O.D.	98 1/4	49 1/8	35 13/16	52 1/4	133
5 Fans	1/2 O.D.	1 1/8 O.D.	7/8 O.D.	115 1/4	57 5/8	53 1/4	52 1/4	159

AIR Defrost Super Low Profile Unit Cooler (SLPA) Specifications

Model No.	Fan Data		Motor Amps		BTUH Capacity @ +25° ST (R22)	
	Qty.	CFM	115V/1Ø	230V/1Ø	10°F TD	12°F TD
SLPA26-51	2	800	2.2	1.1	5,081	6,680
SLPA36-79	3	1,200	3.3	1.7	7,929	9,970
SLPA46-102	4	1,600	4.4	2.2	10,243	13,600
SLPA56-132	5	2,000	5.5	2.8	13,204	17,100
SLPA66-152	6	2,400	6.6	3.3	15,212	19,570

ELECTRIC Defrost Super Low Profile Unit Cooler (SLPE) Specifications

Model No.	Fan Data		Motor Amps 230V/1Ø	Electric Defrost Specs.		BTUH Capacity @ 10°F TD (R404)			
	Qty.	CFM		230V/1Ø	Watts	-30°F ST	-20°F ST	-10°F ST	+10°F ST
SLPE26-51	2	850	1.1	4.1	950	4,100	4,660	5,197	6,690
SLPE36-77	3	1,200	1.7	5.7	1,300	5,790	6,680	7,779	10,600
SLPE46-106	4	1,700	2.2	7.6	1,750	8,890	9,600	10,604	12,300
SLPE56-118	5	2,125	2.8	8.9	2,050	10,200	11,000	11,819	14,000
SLPE66-153	6	2,550	3.3	8.9	2,050	12,100	13,600	15,303	18,500