



VAH120EC
HS120EC
HS120CL-EC

NOTE:
⑤ 0-10 VAC IN (SPEED CTRL)
⑥ 10 VAC OUT

INSTALL POTENTIOMETER
BETWEEN 5 AND 6
TO VARY MOTOR SPEED
or
0-10V DC SPEED
CTRL INPUT

| | | |
|---|-------------|----------|
| UNLESS OTHERWISE SPECIFIED DIMENSION ARE IN INCHES | | |
| TOLERANCES ARE: | | |
| FRACTIONS | DECIMALS | ANGLES |
| ± 1/16 | .X ± .12 | .X ± .5° |
| | .XX ± .06 | |
| | .XXX ± .015 | |
| FIN HEIGHT | FIN LENGTH | |
| ± 1/16 | ± 1/8 | |

LRC COIL CO.

WIRING DIAGRAM
ES-4076EC POT

CAD GENERATED DRAWING,
DO NOT MANUALLY UPDATE
DO NOT SCALE DRAWING

GENERAL SPECS
MATERIAL

| | | |
|--------|---------------|--------------|
| SCALE: | DWG. NO. | REV. |
| | ES-4076EC POT | B |
| DRAWN: | DATE: | SIZE: |
| C.RUA | 4/9/2021 | A |
| | | SHEET 1 OF 1 |

| | | | |
|------|-------------|-----------|-------|
| B | NEW RELEASE | 5/10/2021 | C.RUA |
| REV. | DESCRIPTION | DATE | BY |
| | REVISIONS | | |